

SPECIFICATIONS



base code	DOS M
typology	Recessed Adjustable LED luminaire.
construction	Aluminum Die Cast
reflector finish	Gold (G), Black High Gloss (BG), Silver High Gloss, White (SG), Chrome (C), Black Matt (BM)
trim finish	Black (B)/ White (W)
lamp wattage	12.5W
delivered lumens	1140lm / 1180lm / 1200lm
CCT	2700K / 3000K / 4000K / Tunable White
beam	40°
binning	< 3
CRI	> 90
life	50.000h
IP	IP20
dimming options	Phase-cut Dim, 0-10V, DALI, CASAMBI, Dim to Warm. Power supply to be ordered separately

Base code	A. Wattage	B. Kelvin	C. Beam
DOS M	12 - 12.5 W	27 - 2700K 30 - 3000K 40 - 4000K 50 - Tunable	W - 40°
<p>Base code A B C D E</p> <p>Example: DOS M - 12 30 W G-B DA = DOS M - 12 30 W G-B DA</p>			
D. Reflector & Trim finish		E. Dimming option	
G-B	G-W	ND - Non Dim	
BG-B	BG-W	PC - Phase-cut	
SG-B	SG-W	AD - Analog	
W-B	W-W	DA - Dali	
BM-B	BM-W	D2 - Dali 2	
C-B	C-W	WD - Dim to warm	
		CS - Casambi	

dimension

