

SPECIFICATIONS




base code	DUA
typology	Recessed adjustable LED luminaire, Installation fram included.
construction	Aluminum Die Cast
reflector finish	Gold (G), Black High Gloss (BG), Silver High Gloss (SG), White (W), Chrome (C)
trim finish	Black (B)/ White (W)
lamp wattage	8.5W
delivered lumens	830lm / 860lm / 870lm
CCT	2700K / 3000K / 4000K
beam	40°
binning	< 2
CRI	> 90
life	50.000h
IP	IP20
special features	Variable combination between single, double, triple, quadruple can be made using specific installation frames as shown below
dimming options	Phase-cut Dim, 0-10V, DALI, CASAMBI, Dim to Warm. Power supply to be ordered separately

Base code	A. Wattage	B. Kelvin	C. Beam
DUA	08 - 8.5 W	27 - 2700K 30 - 3000K 40 - 4000K	W - 40°

Base code	A	B	C	D	E
Example: DUA - 08 30 W G-B DA = DUA S - 08 30 W G-B DA					

D. Reflector & Trim finish	E. Dimming option
G-B BG-B SG-B W-B C-B	ND - Non Dim PC - Phase-cut AD - Analog DA - Dali D2 - Dali 2 WD - Dim to warm CS - Casambi
G-W BG-W SG-W W-W C-W	

dimension



installation frames

