

SPECIFICATIONS



base code	DUO M
typology	Recessed Adjustable LED luminaire.
construction	Aluminum Die Cast
reflector finish	Gold (G), Black High Gloss (BG), Silver High Gloss (SG), White (W), Chrome (C), Black Matt (BM)
trim finish	Black (B)/ White (W)
lamp wattage	2 x 12.5W
delivered lumens	2 x 1140lm / 2 x 1180lm / 2 x 1200lm
CCT	2700K / 3000K / 4000K / Tunable White
beam	40°
binning	< 3
CRI	> 90
life	50.000h
IP	IP20
dimming options	Phase-cut Dim, 0-10V, DALI, CASAMBI, Dim to Warm. Power supply to be ordered separately

Base code	A. Wattage	B. Kelvin	C. Beam
DUO M	12 - 12.5 W	27 - 2700K 30 - 3000K 40 - 4000K 50 - Tunable	W - 40°
<p>Base code A B C D E</p> <p>Example: DUO M - 12 30 W G-B DA = DUO M - 12 30 W G-B DA</p>			

D. Reflector & Trim finish

G-B	G-W
BG-B	BG-W
SG-B	SG-W
W-B	W-W
BM-B	BM-W
C-B	C-W

E. Dimming option

ND - Non Dim
PC - Phase-cut
AD - Analog
DA - Dali
D2 - Dali 2
WD - Dim to warm
CS - Casambi

dimension

