

SPECIFICATIONS



| | |
|------------------|---|
| base code | TVO S |
| typology | Recessed Adjustable LED luminaire. |
| construction | Aluminum Die Cast |
| reflector finish | Gold (G), Black High Gloss (BG), Silver High Gloss (SG), White (W), Chrome (C), Black Matt (BC) |
| trim finish | Black (B)/ White (W) |
| lamp wattage | 8.5W |
| delivered lumens | 830lm / 860lm / 870lm |
| CCT | 2700K / 3000K / 4000K |
| beam | 40° |
| binning | < 3 |
| CRI | > 90 |
| life | 50.000h |
| IP | IP20 |
| dimming options | Phase-cut Dim, 0-10V, DALI, Dim to Warm. Power supply to be ordered separately |

| Base code | A. Wattage | B. Kelvin | C. Beam |
|--|------------|--|---------|
| TVO S | 08 - 8.5 W | 27 - 2700K 30 - 3000K 40 - 4000K | W - 40° |
| <p>Example: TVO S - 08 30 W G-B DA = TVO S - 08 30 W G-B DA</p> | | | |

| D. Reflector & Trim finish | E. Dimming option |
|----------------------------|-------------------|
| G-B | ND - Non Dim |
| BG-B | PC - Phase-cut |
| SG-B | AD - Analog |
| W-B | DA - Dali |
| BM-B | D2 - Dali 2 |
| C-B | WD - Dim to warm |
| G-W | |
| BG-W | |
| SG-W | |
| W-W | |
| BM-W | |
| C-W | |

dimension

