

SPECIFICATIONS



base code	UNO M
typology	Recessed LED downlight luminaire
construction	Aluminum Die Cast
reflector finish	Gold (G), Black High Gloss (BG), Silver High Gloss (SG), White (W), Chrome (C)
trim finish	Black (W) / White (W)
lamp wattage	12.5W
delivered lumens	1080lm / 1120lm / 1130lm
CCT	2700K / 3000K / 4000K / Tunable White
beam	35° / 40° / 45°
binning	< 3
CRI	> 90
life	50.000h
IP	IP43/IP20
dimming options	Phase-cut Dim, 0-10V, DALI, CASAMBI, Dim to Warm. Power supply to be ordered separately

Base code	A. Wattage	B. Kelvin	C. Beam	D. Reflector & Trim finish	E. Dimming option
UNO M	12 - 12.5 W	27 - 2700K 30 - 3000K 40 - 4000K 50 - Tunable	M - 35° W - 45°		
Base code A B C D E Example: UNO M - 12 30 M G-B DA = UNO M - 12 30 M G-B DA					
G-B	G-W				ND - Non Dim
BG-B	BG-W				PC - Phase-cut
SG-B	SG-W				AD - Analog
W-B	W-W				DA - Dali
C-B	C-W				D2 - Dali 2
					WD - Dim to warm
					CS - Casambi

